

View Online at <https://aerobasegroup.com/nsn/4320-00-497-5506>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Water, fresh

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal and threaded external

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Submersible

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

4.1 gallons per minute

**Discharge Pressure:**

5.7 pounds per square inch gage

**Total Head:**

13.000 feet

**Operating Speed At Rated Capacity:**

3000.0 revolutions per minute

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.1

**Discharge Connection Thread Size And Series/type Designator:**

0.250-18 npt

**Intake Connection Thread Size And Series/type Designator:**

0.375-18 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

250.0 watts

**Voltage In Volts:**

230.0

**Phase:**

Single

**Frequency In Hertz:**

50.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400