NSN 4320-00-510-9847

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-510-9847

| Prime Mover Quantity: |
|--|
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Current Type: |
| Dc |
| Media For Which Designed: |
| Alcohol |
| Environmental Protection: |
| Explosion proof |
| Pump Quantity: |
| 1 |
| Cooling Method: |
| Self ventilated |
| Maximum Discharge Flow Rate: |
| 0.9 gallons per minute |
| Discharge Pressure: |
| 25.0 pounds per square inch gage |
| Pumping Element Operating Position: |
| Horizontal |
| Rotary Pump Design: |
| Gear |
| Operation Relationship Design: |
| Simultaneous |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Current Rating In Amps: |
| 4.2 |
| Discharge Connection Thread Size And Series/type Designator: |
| 0.250-18 npt |
| Intake Connection Thread Size And Series/type Designator: |
| 0.250-18 npt |
| Voltage In Volts: |
| 27.0 |

NSN 4320-00-510-9847

Rotary Pump Unit - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400