

View Online at <https://aerobasegroup.com/nsn/4320-00-523-6888>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Explosion proof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

1.22 gallons per minute

Discharge Pressure:

40.0 pounds per square inch gage

Total Head:

117.000 feet

Operating Speed At Rated Capacity:

9000.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

0.438 unf

Intake Connection Thread Size And Series/type Designator:

0.562-18 unf

Prime Mover Power Rating:

0.070 horsepower

Voltage In Volts:

27.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400