NSN 4320-00-529-4399

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-529-4399

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Dc
Environmental Protection:
Dust-ignition proof
Pump Quantity:
1
Maximum Discharge Flow Rate:
1.2 gallons per minute
Discharge Pressure:
40.0 pounds per square inch gage
Total Head:
117.000 feet
Operating Speed At Rated Capacity:
9000.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Rotary Pump Design:
Gear
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Discharge Connection Thread Size And Series/type Designator:
0.438-20 unf
Intake Connection Thread Size And Series/type Designator:
0.562-18 unf
Prime Mover Power Rating:
0.070 horsepower
Voltage In Volts:
27.0

27.0

NSN 4320-00-529-4399

Rotary Pump Unit - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400