

View Online at <https://aerobasegroup.com/nsn/4320-00-534-3334>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Skid

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

40.0 gallons per minute

**Total Head:**

58.000 feet

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Discharge Connection Thread Size And Series/type Designator:**

2.000-11-1/2 npt

**Intake Connection Thread Size And Series/type Designator:**

2.000-11-1/2 npt

**Features Provided:**

Self-priming

**Voltage In Volts:**

208.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400