NSN 4320-00-540-6237

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-540-6237

Prime Mover Quantity: 1 Mounting Type: Base Base Stage Quantity: 1 Intake Connection Quantity: 1 Intake Connection Type: Round Itange Discharge Connection Type: Round Itange Media For Which Designed: Water, salt Power Drive Operating Pressure: S75.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Quantity: 1 Single Prime Mover Type: Single Reference Number Differentiating Characteristics: As differentiated by w/power unit Shef Life: Nia		
Mounting Type: Base Stage Quantity: 1 Intake Connection Quantity: 1 Itake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.00 feet Operating Speed At Rated Capacity: 740.0.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Quantity: 1 Single Prime Mover Type: Single Prime Mover Type: Single Prime Mover Type: Single Prime Mo	Prime Mover Quantity:	
Base Stage Quantiy: 1 Intake Connection Quantiy: 1 Itake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Impeller Quantity: 1 Catifical Flow Type: Single Prime Mover Type: Single Prime Mover Type: Start Utbine As differentiated by wypower unit Shel Lie: Na		
Stage Quantity: 1 Intake Connection Quantity: 1 Intake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximun Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Staet nurbline Reference Number Differentiating Characteristics: As differentiated by w/power unit Shiff Life: Na		
1 Intake Connection Quantity: 1 Intake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Single <		
Itake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 150.0 gallons per minute 150.0 gallons per minute 150.0 gallons per minute Portating Speed At Rated Capacity: 740.0 revolutions per minute Punging Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Single Prime Mover Type: Single Prime Mover Type: Single Prime Mover Type: Sitean turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shef Life: Na		
1 Intake Connection Type: Round Ifange Discharge Connection Quantity: 1 Discharge Connection Type: Round Ifange Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Sizant urbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shef Life: Na		
Itake Connection Type: Round fiange Discharge Connection Quantity: 1 Discharge Connection Type: Round fiange Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Single Prime Mover Type: Single Reference Number Differentiating Characteristics: As differentiated by w/power unit Sher Life: Na		
Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Vater, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Inselier Quantity: 1 Centrifugal Pump Inselier Quantity: 1 Single Prime Mover Type: Single Prime Mover Type: Start urbine At differentiated by w/power unit Shif Life: Na		
Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximu Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Impeller Quantity: 1 1 Centrifugal Pump Impeller Quantity: 1 Single Prime Mover Type: Single Prime Mover Type: Start urbine At differentiated by w/power unit Shiff Life: Na		
1 Discharge Connection Type: Round flange Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Single Prime Mover Type: Single Arifurdia Pump Impeller Suction Type: Single Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Sheft Life: Na	-	
Discharge Connection Type:Round flangeMedia For Which Designed:Water, saltPower Drive Operating Pressure:575.0 pounds per square inch gagePump Quantity:1Maximum Discharge Flow Rate:150.0 gallons per minuteTotal Head:1770.000 feetOperating Speed At Rated Capacity:7400 revolutions per minutePumping Element Operating Position:HorizontalCentrifugal Pump Impeller Quantity:1Centrifugal Pump Impeller Quantity:1SinglePrime Mover Type:Steam turbineKaferentiated by w/power unitShiff Lifferentiating Characteristics:As differentiated by w/power unitShiff Lifferentiation Characteristics:Na	Discharge Connection Quantity:	
Round flage Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Single Prime Mover Type: Single Prime Mover Type: Steam turbine Raferenciated by w/power unit Sheff Life: Na		
Media For Which Designed: Water, salt Power Drive Operating Pressure: 575.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Single Prime Mover Type: Single Prime Mover Type: Steam turbine Raferenciated by w/power unit Sheff Life: N/a		
Water, saltPower Drive Operating Pressure:575.0 pounds per square inch gagePump Quantity:1Maximum Discharge Flow Rate:150.0 gallons per minuteTotal Head:1770.000 feetOperating Speed At Rated Capacity:7400.0 revolutions per minutePumping Element Operating Position:HorizontalCentrifugal Pump Design:Radial flowCentrifugal Pump Impeller Quantity:1SinglePrime Mover Type:SinglePrime Mover Type:Steam turbineReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	-	
Power Drive Operating Pressure:575.0 pounds per square inch gagePump Quantity:1Maximun Discharge Flow Rate:150.0 gallons per minuteTotal Head:1770.000 feetOperating Speed At Rated Capacity:7400.0 revolutions per minutePumping Element Operating Position:HorizontalCentrifugal Pump Design:Radial flowCentrifugal Pump Impeller Quantity:1SinglePrime Mover Type:SinglePrime Mover Type:Steam turbineAdiferentiated by w/power unitSheff Life:Nya	Media For Which Designed:	
575.0 pounds per square inch gagePump Quantity:1Maximum Discharge Flow Rate:150.0 gallons per minuteTotal Head:1770.000 feetOperating Speed At Rated Capacity:7400.0 revolutions per minutePumping Element Operating Position:HorizontalCentrifugal Pump Design:Radial flowCentrifugal Pump Impeller Quantity:1SinglePrime Mover Type:SingleReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	Water, salt	
Pump Quantity: 1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Single Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	Power Drive Operating Pressure:	
1 Maximum Discharge Flow Rate: 150.0 gallons per minute Total Head: 1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute Pumping Element Operating Position: 14orizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	575.0 pounds per square inch gage	
Maximum Discharge Flow Rate:150.0 gallons per minuteTotal Head:1770.000 feetOperating Speed At Rated Capacity:7400.0 revolutions per minutePumping Element Operating Position:HorizontalCentrifugal Pump Design:Radial flowCentrifugal Pump Impeller Quantity:1Centrifugal Pump Impeller Suction Type:SinglePrime Mover Type:Steam turbineReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	Pump Quantity:	
150.0 gallons per minuteTotal Head:1770.000 feetOperating Speed At Rated Capacity:7400.0 revolutions per minutePumping Element Operating Position:HorizontalCentrifugal Pump Design:Radial flowCentrifugal Pump Impeller Quantity:1Centrifugal Pump Impeller Suction Type:SinglePrime Mover Type:Steam turbineReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	1	
Total Head:1770.000 feetOperating Speed At Rated Capacity:7400.0 revolutions per minutePumping Element Operating Position:HorizontalCentrifugal Pump Design:Radial flowCentrifugal Pump Impeller Quantity:1SinglePrime Mover Type:Steam turbineReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	Maximum Discharge Flow Rate:	
1770.000 feet Operating Speed At Rated Capacity: 7400.0 revolutions per minute 7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Single Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	150.0 gallons per minute	
Operating Speed At Rated Capacity:7400.0 revolutions per minutePumping Element Operating Position:HorizontalCentrifugal Pump Design:Radial flowCentrifugal Pump Impeller Quantity:1Centrifugal Pump Impeller Suction Type:SinglePrime Mover Type:Steam turbineReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	Total Head:	
7400.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	1770.000 feet	
Pumping Element Operating Position:HorizontalCentrifugal Pump Design:Radial flowCentrifugal Pump Impeller Quantity:1Centrifugal Pump Impeller Suction Type:SinglePrime Mover Type:Steam turbineReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	Operating Speed At Rated Capacity:	
Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	7400.0 revolutions per minute	
Centrifugal Pump Design:Radial flowCentrifugal Pump Impeller Quantity:1Centrifugal Pump Impeller Suction Type:SinglePrime Mover Type:Steam turbineReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	Pumping Element Operating Position:	
Radial flowCentrifugal Pump Impeller Quantity:1Centrifugal Pump Impeller Suction Type:SinglePrime Mover Type:Steam turbineReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	Horizontal	
Centrifugal Pump Impeller Quantity:1Centrifugal Pump Impeller Suction Type:SinglePrime Mover Type:Steam turbineReference Number Differentiating Characteristics:As differentiated by w/power unitShelf Life:N/a	Centrifugal Pump Design:	
1 Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	Radial flow	
Centrifugal Pump Impeller Suction Type: Single Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	Centrifugal Pump Impeller Quantity:	
Single Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	1	
Prime Mover Type: Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	Centrifugal Pump Impeller Suction Type:	
Steam turbine Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	Single	
Reference Number Differentiating Characteristics: As differentiated by w/power unit Shelf Life: N/a	Prime Mover Type:	
As differentiated by w/power unit Shelf Life: N/a	Steam turbine	
Shelf Life: N/a	Reference Number Differentiating Characteristics:	
N/a	As differentiated by w/power unit	
	Shelf Life:	
Unit Of Measure:	N/a	
	Unit Of Measure:	

--

NSN 4320-00-540-6237

Centrifugal Pump Unit - Page 2 of 2

Demilitarization:

No

Fiig:

A19400

