NSN 4320-00-541-1956

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-541-1956

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Brine
Environmental Protection:
Splash proof
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
160.0 gallons per minute
Total Head:
81.000 feet
Operating Speed At Rated Capacity:
1750.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
, 511010000

NSN 4320-00-541-1956

Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:
11.0
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400