

View Online at <https://aerobasegroup.com/nsn/4320-00-541-8462>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

2

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, salt and water, fresh

**Environmental Protection:**

Dripproof

**Pump Quantity:**

2

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

350.0 gallons per minute and 150.0 gallons per minute

**Total Head:**

50.000 feet

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

2

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

14.0

**Features Provided:**

Self-priming

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

As differentiated by left hand

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400