NSN 4320-00-555-8932

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-555-8932

Prime Mover Quantity:
1
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Environmental Protection:
Dripproof
Pump Quantity:
1
Maximum Discharge Flow Rate:
57.0 gallons per minute
Total Head:
80.800 feet
Operating Speed At Rated Capacity:
3500.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
Prime Mover Power Rating:
2.500 horsepower
Voltage In Volts:
440.0
Phase:
Three

NSN 4320-00-555-8932

Centrifugal Pump Unit - Page 2 of 2



60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400