NSN 4320-00-579-3429

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-579-3429

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Hydrocarbon fuels and oils
Environmental Protection:
Splash proof
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
50.0 gallons per minute
Discharge Pressure:
50.0 pounds per square inch gage
Operating Speed At Rated Capacity:
520.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Rotary Pump Design:
Vane
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:
4.5
Voltage In Volts:
440.0
Phase:
Three

NSN 4320-00-579-3429

Rotary Pump Unit - Page 2 of 2



Frequency	In I	Hertz:
-----------	------	--------

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400