NSN 4320-00-580-6168

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-580-6168

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Hydrocarbon fuels and oils
Mounting Type:
Base
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Dc
Media For Which Designed:
Hydrocarbon fuels and oils
Pump Quantity:
1
Maximum Discharge Flow Rate:
0.5 gallons per minute
Discharge Pressure:
15.0 pounds per square inch gage
Operating Speed At Rated Capacity:
9700.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Rotary Pump Design:
Gear
Operation Relationship Design:
Simultaneous
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Discharge Connection Thread Size And Series/type Designator:
0.562-18 unf
Intake Connection Thread Size And Series/type Designator:
0.562-18 unf
Prime Mover Power Rating:
0.083 horsepower

NSN 4320-00-580-6168

Rotary Pump Unit - Page 2 of 2



Voltage	In \	Volts:
---------	------	--------

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400