## NSN 4320-00-585-0336

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-585-0336

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Dc
Media For Which Designed:
Oil
Environmental Protection:
Dripproof
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
40.0 gallons per minute
Discharge Pressure:
40.0 pounds per square inch gage
Operating Speed At Rated Capacity:
1750.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Rotary Pump Design:
Screw
Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
Current Rating In Amps:
14.9
Prime Mover Power Rating:
5.000 horsepower
Voltage In Volts:
250.0

## NSN 4320-00-585-0336

Rotary Pump Unit - Page 2 of 2



c	pecif	icati	on	Or	C+2	nd	ard	ı
3	becn	icati	on '	Ul I	ota	na	arc	1.

3 type and 01 class

**Reference Number Differentiating Characteristics:** 

As differentiated by dc motor, not provided w/controller

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A19400