

View Online at <https://aerobasegroup.com/nsn/4320-00-585-2591>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Unthreaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded internal

Current Type:

Ac

Media For Which Designed:

Oil

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

3.0 gallons per minute

Discharge Pressure:

500.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1150.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Vane

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

3.3

Prime Mover Power Rating:

2.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated w/electro dynamics motor dwg no. D-83-941-63

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400