

View Online at <https://aerobasegroup.com/nsn/4320-00-591-5183>

Prime Mover Quantity:

1

Stage Quantity:

1

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Current Type:

Ac

Environmental Protection:

Splashtight

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

80.0 gallons per minute

Suction Lift:

20.000 feet

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Discharge Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

0.750 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

Media for which designed: diphenyl

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400