

View Online at <https://aerobasegroup.com/nsn/4320-00-600-7590>

**Mounting Type:**

Wheel

**Discharge Connection Flange Thickness:**

0.375 inches

**Prime Mover Horsepower Rating:**

36.000

**Suction Connection Quick Disconnect Style:**

Cam or lever

**Prime Mover Type:**

Gasoline engine

**Discharge Connection Type:**

Flanged or quick disconnect

**Capacity Rating:**

350.0 gallons per minute

**Suction Connection Type:**

Flanged and quick disconnect

**Pump Type:**

Centrifugal

**Suction Connection Flange Type:**

Drilled

**Suction Connection Flange Thickness:**

0.375 inches

**Suction Connection Flange Bolt Circle Diameter:**

5.875 inches

**Suction Connection Flange Bolt Hole Quantity:**

8

**Suction Connection Flange Bolt Hole Diameter:**

0.438 inches

**Suction Connection Quick Disconnect Size:**

4 in.

**Discharge Connection Flange Bolt Circle Diameter:**

5.875 inches

**Discharge Connection Flange Bolt Hole Quantity:**

8

**Discharge Connection Flange Bolt Hole Diameter:**

0.438 inches

**Discharge Connection Quick Disconnect Size:**

4 in.

**Explosion Proof Feature:**

Not included

**Discharge Connection Flange Type:**

Drilled

**Ground Cable:**

Included

**Cable Reel:**

Not included

**Water Remover Type:**

Strainer

**Drum Emptying Manifold Assembly:**

Not included

**Discharge Connection Quick Disconnect Style:**

Cam or lever

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T103-m