NSN 4320-00-618-2631

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-618-2631

| Manustina Tuna |
|--|
| Mounting Type: |
| Base |
| Intake Connection Quantity: |
| 1 Intelle Connection Times |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Drive Connection Type: |
| Gear |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| Maximum Discharge Flow Rate: |
| 0.9 gallons per minute and 0.8 gallons per minute |
| Discharge Pressure: |
| 3.5 pounds per square inch gage and 0.05 pounds per square inch gage |
| Operating Speed At Rated Capacity: |
| 2570.0 revolutions per minute and 975.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Pump Rotation Direction: |
| Clockwise |
| Volume Control Type: |
| Rotary |
| Rotary Pump Design: |
| Gear |
| Operation Method: |
| Powered |
| Drive Shaft Type: |
| Splined, straight external |
| Drive Shaft Length: |
| 0.094 inches |
| Discharge Connection Thread Size And Series/type Designator: |
| 0.250-20 npt |
| Intake Connection Thread Size And Series/type Designator: |
| 0.250-20 npt |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4320-00-618-2631

Rotary Pump - Page 2 of 2



Demilitarization:

No

Fiig:

A19400