

View Online at <https://aerobasegroup.com/nsn/4320-00-640-0503>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Any acceptable

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Any acceptable

Pump Quantity:

1

Cooling Method:

Any acceptable

Maximum Discharge Flow Rate:

2.0 gallons per minute

Discharge Pressure:

Not rated

Total Head:

29.500 feet

Suction Lift:

Not rated

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Rotary Pump Design:

Vane

Prime Mover Horsepower Rating:

0.250

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

Any acceptable

Discharge Connection Thread Size And Series/type Designator:

Any acceptable

Intake Connection Thread Size And Series/type Designator:

0.750-14 npt

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400