

View Online at <https://aerobasegroup.com/nsn/4320-00-654-3617>

Mounting Type:

Base

Intake Connection Quantity:

3

Intake Connection Type:

Square flange

Discharge Connection Quantity:

3

Discharge Connection Type:

Threaded internal and square flange

Drive Connection Type:

Gear

Media For Which Designed:

Hydrocarbon fuels and oils

Maximum Discharge Flow Rate:

11.6 gallons per minute and 10.4 gallons per minute and 1.7 gallons per minute

Discharge Pressure:

600.0 pounds per square inch gage and 150.0 pounds per square inch gage

Total Head:

550.000 feet

Suction Lift:

15.000 feet

Operating Speed At Rated Capacity:

3250.0 revolutions per minute and 450.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Counterclockwise

Rotary Pump Design:

Gear

Operation Method:

Powered

Drive Shaft Type:

Splined, straight external

Drive Shaft End Diameter:

Between 0.645 inches and 0.650 inches

Drive Shaft Length:

Between 1.051 inches and 1.181 inches

Discharge Connection Thread Size And Series/type Designator:

0.875-14 unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400