

View Online at <https://aerobasegroup.com/nsn/4320-00-684-0815>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Inside Diameter:**

Between 1.626 inches and 1.628 inches

**Outside Diameter:**

2.375 inches

**Material Thickness:**

0.094 inches

**Mounting Hole Quantity:**

2

**Angle Between Centerlines Of Mounting Holes In Deg:**

180.0

**Mounting Hole Type:**

Threaded

**Body Length:**

0.750 inches

**Special Features:**

Mtg holes located on od at 90.0 degrees to bore

**Material:**

Steel, qq-s-763

**Material:**

Steel comp 202 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 633 or steel comp 634 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 440fse or steel comp 446

**Material Specification:**

Qq-s-763 federal specification single material response

**Style Designator:**

Round

**Thread Size And Series/type Designator:**

0.250-20 unc

**Fsc Application Data:**

Centrifugal pump

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23700