

View Online at <https://aerobasegroup.com/nsn/4320-00-689-3192>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

47.0 gallons per minute

Discharge Pressure:

175.0 pounds per square inch gage

Total Head:

26.000 feet

Suction Lift:

15.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Length:

19.250 inches

Unpackaged Unit Width:

7.5000 inches

Unpackaged Unit Height:

11.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

1.6 and 0.8

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

0.250 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A19400