## NSN 4320-00-689-3192

Centrifugal Pump Unit - Page 1 of 2

**Prime Mover Quantity:** 



View Online at https://aerobasegroup.com/nsn/4320-00-689-3192

| Prime Mover Cooling Medium:               |
|---|
| Air                                       |
| Mounting Type:                            |
| Base                                      |
| Stage Quantity:                           |
| 1   |
| Intake Connection Quantity:               |
| 1   |
| Intake Connection Type:                   |
| Threaded internal                         |
| Discharge Connection Quantity:            |
| 1   |
| Discharge Connection Type:                |
| Threaded internal                         |
| Current Type:                             |
| Ac  |
| Media For Which Designed:                 |
| Water, fresh                              |
| Environmental Protection:                 |
| Dripproof                                 |
| Pump Quantity:                            |
| 1   |
| Cooling Method:                           |
| Self ventilated                           |
| Maximum Discharge Flow Rate:              |
| 47.0 gallons per minute                   |
| Discharge Pressure:                       |
| 175.0 pounds per square inch gage         |
| Total Head:                               |
| 26.000 feet                               |
| Suction Lift:                             |
| 15.000 feet                               |
| Operating Speed At Rated Capacity:        |
| 1750.0 revolutions per minute             |
| Centrifugal Pump Design:                  |
| Radial flow                               |
| Centrifugal Pump Impeller Quantity:       |
|   |
| 1   |
| 1 Centrifugal Pump Impeller Suction Type: |
| •   |
| Centrifugal Pump Impeller Suction Type:   |

## **NSN 4320-00-689-3192** Centrifugal Pump Unit - Page 2 of 2



| Unpackaged Unit Length:                                      |
|--|
| 19.250 inches  |
| Unpackaged Unit Width:                                       |
| 7.5000 inches  |
| Unpackaged Unit Height:                                      |
| 11.000 inches  |
| Prime Mover Type:  |
| Electric motor   |
| nclosure Type:   |
| Open   |
| Current Rating In Amps:                                      |
| 1.6 and 0.8  |
| Discharge Connection Thread Size And Series/type Designator: |
| 1.250-11-1/2 npt   |
| ntake Connection Thread Size And Series/type Designator:     |
| 1.250-11-1/2 npt   |
| Prime Mover Power Rating:                                    |
| 0.250 horsepower   |
| Voltage In Volts:  |
| 115.0 and 230.0  |
| Phase:   |
| Single   |
| Frequency In Hertz:  |
| 60.0   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |
| Filg:  |
| 419400   |
|  |