

View Online at <https://aerobasegroup.com/nsn/4320-00-690-2038>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Cylinder Quantity:

1

Intake Connection Quantity:

2

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

2

Discharge Connection Type:

Threaded internal

Current Type:

Ac/dc

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

Pumping Element Type:

Piston

Cooling Method:

Air to air cooled

Operating Speed At Rated Capacity:

6000.0 revolutions per minute and 12000.0 revolutions per minute

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Pressure compensation

Control Location:

Center

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

55.0 and 27.5

Discharge Connection Thread Size And Series/type Designator:

1.312-12 un

Intake Connection Thread Size And Series/type Designator:

1.312-12 un

Voltage In Volts:

200.0

Reference Number Differentiating Characteristics:

As differentiated by source controlling dwg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400