

View Online at <https://aerobasegroup.com/nsn/4320-00-717-1138>

Prime Mover Quantity:

1

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Unthreaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Submersible

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

1.3 gallons per minute

Operating Speed At Rated Capacity:

6600.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

3.0

Discharge Connection Thread Size And Series/type Designator:

0.750-16 unf

Features Provided:

Self-priming

Voltage In Volts:

28.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400