NSN 4320-00-717-1138

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-717-1138

Prime Mover Quantity:
1
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Unthreaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Dc
Media For Which Designed:
Hydrocarbon fuels and oils
Environmental Protection:
Submersible
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
1.3 gallons per minute
Operating Speed At Rated Capacity:
6600.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Centrifugal Pump Design:
Axial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Operation Relationship Design:
Simultaneous
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:

NSN 4320-00-717-1138

Centrifugal Pump Unit - Page 2 of 2

Fiig: A19400



Discharge Connection Thread Size And Series/type Designator:
0.750-16 unf
Features Provided:
Self-priming
Voltage In Volts:
28.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No