NSN 4320-00-720-0830

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-720-0830

Prime Mover Quantity: Stage Quantity: Intake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Stage Quantity: Intake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Intake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Intake Connection Quantity: Intake Connection Type: Round flange Discharge Connection Quantity: Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Intake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Intake Connection Type: Round flange Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Discharge Connection Quantity: 1 Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Discharge Connection Quantity: Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Discharge Connection Type: Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Round flange Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Media For Which Designed: Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Hydrocarbon fuels and oils Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Power Drive Operating Pressure: 45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
45.0 pounds per square inch gage Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Pump Quantity: 1 Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Maximum Discharge Flow Rate: 25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
25.0 gallons per minute Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Total Head: 96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
96.600 feet Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Suction Lift: 23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
23.700 feet Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
Operating Speed At Rated Capacity: 3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity: 1
3500.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Horizontal Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Centrifugal Pump Design: Radial flow Centrifugal Pump Impeller Quantity:
Radial flow Centrifugal Pump Impeller Quantity: 1
Centrifugal Pump Impeller Quantity:
1
•
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Water turbine
Shelf Life:
N/a
N/a Unit Of Measure:
. 7 -

No

NSN 4320-00-720-0830

Centrifugal Pump Unit - Page 2 of 2



Fiig:

A19400