NSN 4320-00-725-1939

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-725-1939

Prime Mover Quantity:
1
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Water, salt
Environmental Protection:
Submersible
Pump Quantity:
1
Maximum Discharge Flow Rate:
585.0 gallons per minute
Discharge Pressure:
25.0 pounds per square inch gage
Total Head:
56.000 feet
Operating Speed At Rated Capacity:
1750.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Prime Mover Power Rating:
15.000 horsepower

NSN 4320-00-725-1939

Centrifugal Pump Unit - Page 2 of 2



Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400