## NSN 4320-00-728-3847

Reciprocating Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-728-3847

Prime Mover Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Media For Which Designed:
Hydrocarbon fuels and oils
Environmental Protection:
Dripproof
Pump Quantity:
1
Pumping Element Type:
Piston
Maximum Discharge Flow Rate:
4.0 gallons per minute
Discharge Pressure:
1500.0 pounds per square inch gage
Operating Speed At Rated Capacity:
1800.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Reciprocating Stroke Type:
Variable
Volume Control Type:
Pressure compensation
Control Location:
Center
Prime Mover Type:
Electric motor
Prime Mover Power Rating:
5.000 horsepower
Voltage In Volts:
220.0
Phase:
Three

## NSN 4320-00-728-3847

Reciprocating Pump Unit - Page 2 of 2



Frequency I	n H	lertz:
-------------	-----	--------

60.0

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400