NSN 4320-00-728-3847

Reciprocating Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-728-3847

Prime Mover Quantity:		
1		
Intake Connection Quantity:		
1		
Intake Connection Type:		
Threaded internal		
Discharge Connection Quantity:		
1		
Discharge Connection Type:		
Threaded internal		
Current Type:		
Ac		
Media For Which Designed:		
Hydrocarbon fuels and oils		
Environmental Protection:		
Dripproof		
Pump Quantity:		
1		
Pumping Element Type:		
Piston		
Maximum Discharge Flow Rate:		
4.0 gallons per minute		
Discharge Pressure:		
1500.0 pounds per square inch gage		
Operating Speed At Rated Capacity:		
1800.0 revolutions per minute		
Pumping Element Operating Position:		
Horizontal		
Reciprocating Stroke Type:		
Variable		
Volume Control Type:		
Pressure compensation		
Control Location:		
Center		
Prime Mover Type:		
Electric motor		
Prime Mover Power Rating:		
5.000 horsepower		
Voltage In Volts:		
220.0		
Phase:		
Three		

NSN 4320-00-728-3847

Reciprocating Pump Unit - Page 2 of 2

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A19400

