

View Online at <https://aerobasegroup.com/nsn/4320-00-733-1382>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Cylinder Quantity:**

7

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Dc

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Waterproof

**Pump Quantity:**

1

**Pumping Element Type:**

Piston

**Cooling Method:**

Air to air cooled

**Discharge Pressure:**

7.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

750.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Pump Reciprocating Design:**

Double acting

**Reciprocating Stroke Type:**

Variable

**Volume Control Type:**

Pressure compensation

**Control Location:**

Right side

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

0.125-27 nptf

**Intake Connection Thread Size And Series/type Designator:**

0.125-27 nptf

**Prime Mover Power Rating:**

0.013 horsepower

**Voltage In Volts:**

24.0

**Special Features:**

Designed for automotive fuel systems

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400