

View Online at <https://aerobasegroup.com/nsn/4320-00-733-1382>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Cylinder Quantity:

7

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Waterproof

Pump Quantity:

1

Pumping Element Type:

Piston

Cooling Method:

Air to air cooled

Discharge Pressure:

7.0 pounds per square inch gage

Operating Speed At Rated Capacity:

750.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Pump Reciprocating Design:

Double acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Pressure compensation

Control Location:

Right side

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

0.125-27 nptf

Intake Connection Thread Size And Series/type Designator:

0.125-27 nptf

Prime Mover Power Rating:

0.013 horsepower

Voltage In Volts:

24.0

Special Features:

Designed for automotive fuel systems

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400