NSN 4320-00-741-7538

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-741-7538

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Media For Which Designed:
Water, fresh
Environmental Protection:
Dripproof
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
110.0 gallons per minute
Discharge Pressure:
125.0 pounds per square inch gage
Total Head:
16.000 feet
Operating Speed At Rated Capacity:
1750.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
LICOTIO IIIOTOI

NSN 4320-00-741-7538Centrifugal Pump Unit - Page 2 of 2



Inclosure Type:	
Open	
Discharge Connection Thread Size And Series/type Designator:	
3.000-8 npt	
Intake Connection Thread Size And Series/type Designator:	
3.00-8 npt	
Voltage In Volts:	
115.0	
Phase:	
Single	
Frequency In Hertz:	
60.0	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A19400	