

View Online at <https://aerobasegroup.com/nsn/4320-00-752-9647>

Prime Mover Quantity:

1

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Submersible

Pump Quantity:

1

Maximum Discharge Flow Rate:

180.0 gallons per minute

Total Head:

50.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

2.500-8 npt

Intake Connection Thread Size And Series/type Designator:

2.500-8 npt

Prime Mover Power Rating:

5.000 horsepower

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by nonmagnetic type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400