

View Online at <https://aerobasegroup.com/nsn/4320-00-756-5703>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Frame

Intake Connection Quantity:

1

Intake Connection Type:

Unthreaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

18.0 gallons per minute

Discharge Pressure:

1300.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Unpackaged Unit Length:

20.0000 inches

Unpackaged Unit Width:

20.0000 inches

Unpackaged Unit Height:

51.300 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

20.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400