## NSN 4320-00-768-0470

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-768-0470

Thread Direction:
Right-hand and right-hand
Torque Load Rating:
95.3 inch-pounds
Mounting Type:
Flange
Keyway Width:
0.312 inches
Mounting Hole Diameter:
0.500 inches
Mounting Hole Quantity:
9
Thread Size:
1.875-12 and 1.875-12 and 1.312-12
Shaft Diameter:
Between 1.150 inches and 1.249 inches
Operating Speed At Rated Capacity In Rpm:
1600.0
Mounting Bolt Circle Diameter:
5.625 inches
Drive Shaft Type:
Machine keyway
Housing Material:
Cast iron qq-i-652 class 40
Screw Thread Series Designator:
Un and un and un
Shaft Rotation Direction:
Clockwise and counterclockwise
Thread Location:
Internal and internal and internal
Shaft Protrusion Length:
2.062 inches
Connection Quantity:
3
Connection Type:
Inlet and outlet and drain
Maximum Working Pressure Rating At Specificationified Tempurature Range:
3000 psi at minus 40 degrees f to plus 160 degrees f
Connection Design:
Threaded and threaded
Displacement Type:
Constant

## **NSN 4320-00-768-0470** Hydraulic Motor - Page 2 of 2



Constant Displacement Per Revolution:
5.980 cubic inches
Connection Government Specification/std:
Ms 16142
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T103-f