

View Online at <https://aerobasegroup.com/nsn/4320-00-768-0470>

**Thread Direction:**

Right-hand and right-hand and right-hand

**Torque Load Rating:**

95.3 inch-pounds

**Mounting Type:**

Flange

**Keyway Width:**

0.312 inches

**Mounting Hole Diameter:**

0.500 inches

**Mounting Hole Quantity:**

9

**Thread Size:**

1.875-12 and 1.875-12 and 1.312-12

**Shaft Diameter:**

Between 1.150 inches and 1.249 inches

**Operating Speed At Rated Capacity In Rpm:**

1600.0

**Mounting Bolt Circle Diameter:**

5.625 inches

**Drive Shaft Type:**

Machine keyway

**Housing Material:**

Cast iron qq-i-652 class 40

**Screw Thread Series Designator:**

Un and un and un

**Shaft Rotation Direction:**

Clockwise and counterclockwise

**Thread Location:**

Internal and internal and internal

**Shaft Protrusion Length:**

2.062 inches

**Connection Quantity:**

3

**Connection Type:**

Inlet and outlet and drain

**Maximum Working Pressure Rating At Specificationified Tempurature Range:**

3000 psi at minus 40 degrees f to plus 160 degrees f

**Connection Design:**

Threaded and threaded and threaded

**Displacement Type:**

Constant

**Constant Displacement Per Revolution:**

5.980 cubic inches

**Connection Government Specification/std:**

Ms 16142

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T103-f