

View Online at <https://aerobasegroup.com/nsn/4320-00-803-5656>

Prime Mover Quantity:

2

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1 and 1

Intake Connection Quantity:

2

Intake Connection Type:

Round flange

Discharge Connection Quantity:

2

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Ethylene glycol

Environmental Protection:

Dripproof

Pump Quantity:

2

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

80.0 gallons per minute and 80.0 gallons per minute

Discharge Pressure:

100.0 pounds per square inch gage and 100.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3500.0 revolutions per minute and 3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

2

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

37.800 inches

Unpackaged Unit Width:

35.0000 inches

Unpackaged Unit Height:

22.600 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

20.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400