NSN 4320-00-810-1954

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-810-1954

Prime Mover Quantity:
1
Mounting Type:
Skid
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Dc
Media For Which Designed:
Water, fresh and water, salt
Environmental Protection:
Waterproof
Pump Quantity:
1
Maximum Discharge Flow Rate:
175.0 gallons per minute
Total Head:
100.000 feet
Suction Lift:
10.000 feet
Operating Speed At Rated Capacity:
3450.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed

NSN 4320-00-810-1954

Centrifugal Pump Unit - Page 2 of 2



Features Provided:
Self-priming
Prime Mover Power Rating:
7.5 horsepower
Voltage In Volts:
115.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400