NSN 4320-00-812-7345

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-812-7345

| Prime Mover Quantity: |
|--|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| Environmental Protection: |
| Waterproof |
| Pump Quantity: |
| 1 |
| Cooling Method: |
| Blower cooled |
| Maximum Discharge Flow Rate: |
| 3.0 gallons per minute |
| Discharge Pressure: |
| 200.0 pounds per square inch gage |
| Total Head: |
| 435.000 feet |
| Operating Speed At Rated Capacity: |
| 1800.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Rotary Pump Design: |
| Gear |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Discharge Connection Thread Size And Series/type Designator: |
| 0.500-14 npt |
| Intake Connection Thread Size And Series/type Designator: |
| 0.500-14 npt |
| |

NSN 4320-00-812-7345Rotary Pump Unit - Page 2 of 2



| Prime Mover Power Rating: |
|---------------------------|
| 0.333 horsepower |
| Voltage In Volts: |
| 120.0 |
| Phase: |
| Single |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A19400