

View Online at <https://aerobasegroup.com/nsn/4320-00-816-4448>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

2

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Round flange

**Current Type:**

Dc

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Splash proof

**Pump Quantity:**

2

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

100.0 gallons per minute

**Total Head:**

46.000 feet

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

2

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

19.2

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

5.000 horsepower

**Voltage In Volts:**

250.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400