NSN 4320-00-820-5783

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-820-5783

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
2
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Hydrocarbon fuels and oils
Environmental Protection:
Explosion proof
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
425.0 gallons per minute
Total Head:
577.000 feet
Operating Speed At Rated Capacity:
3500.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
2
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed

NSN 4320-00-820-5783Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:	
155.0	
Voltage In Volts:	
440.0	
Phase:	
Three	
Frequency In Hertz:	
60.0	
Reference Number Differentiating Characteristics:	
Furnished w/o repair parts	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
Δ19400	