NSN 4320-00-823-6626

Rotary Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-00-823-6626

Intake Connection Quantity: Intake Connection Type: Threaded internal Discharge Connection Quantity: I Drive Connection Type: Gear Media For Which Designed: Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring Shelf Life:
Intake Connection Type: Threaded internal Discharge Connection Quantity: 1 Drive Connection Type: Gear Media For Which Designed: Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Intake Connection Type: Threaded internal Discharge Connection Quantity: 1 Drive Connection Type: Gear Media For Which Designed: Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Threaded internal Discharge Connection Quantity: 1 Drive Connection Type: Gear Media For Which Designed: Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Discharge Connection Quantity: 1 Drive Connection Type: Gear Media For Which Designed: Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Drive Connection Type: Gear Media For Which Designed: Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Drive Connection Type: Gear Media For Which Designed: Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Media For Which Designed: Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Media For Which Designed: Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Hydrocarbon fuels and oils Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Pump Rotation Direction: Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Counterclockwise Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Rotary Pump Design: Screw Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Operation Method: Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Powered Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Drive Shaft Type: Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Splined, straight external Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Drive Shaft End Diameter: Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Between 0.412 inches and 0.417 inches Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Drive Shaft Length: Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Between 0.625 inches and 0.745 inches Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Intake Connection Thread Size And Series/type Designator: 1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
1.312-12 un Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Features Provided: Integral relief valve Special Features: Discharge connection type: o-ring
Integral relief valve Special Features: Discharge connection type: o-ring
Special Features: Discharge connection type: o-ring
Discharge connection type: o-ring
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A19400