## NSN 4320-00-825-3532

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-825-3532

| Prime Mover Quantity:                   |
|---|
| 1                                       |
| Prime Mover Cooling Medium:             |
| Air                                     |
| Stage Quantity:                         |
| 1                                       |
| Intake Connection Quantity:             |
| 1                                       |
| Intake Connection Type:                 |
| Round flange                            |
| Discharge Connection Quantity:          |
| 1                                       |
| Discharge Connection Type:              |
| Round flange                            |
| Current Type:                           |
| Ac                                      |
| Media For Which Designed:               |
| Water, salt                             |
| Environmental Protection:               |
| Dripproof                               |
| Pump Quantity:                          |
| 1                                       |
| Cooling Method:                         |
| Self ventilated                         |
| Maximum Discharge Flow Rate:            |
| 1.0 gallons per minute                  |
| Total Head:                             |
| 70.000 feet                             |
| Operating Speed At Rated Capacity:      |
| 3500.0 revolutions per minute           |
| Pumping Element Operating Position:     |
| Vertical                                |
| Centrifugal Pump Design:                |
| Radial flow                             |
| Centrifugal Pump Impeller Quantity:     |
| 1                                       |
| Centrifugal Pump Impeller Suction Type: |
| Single                                  |
| Prime Mover Type:                       |
| Electric motor                          |
| Inclosure Type:                         |
| Partially enclosed                      |
|   |

## NSN 4320-00-825-3532

Centrifugal Pump Unit - Page 2 of 2



**Current Rating In Amps:** 

2.5

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

## **Reference Number Differentiating Characteristics:**

As differentiated by low pressure brine pump, and furnishedwithout repair parts

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A19400