

View Online at <https://aerobasegroup.com/nsn/4320-00-830-4001>

Prime Mover Quantity:

1

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Dust-ignition proof

Pump Quantity:

1

Maximum Discharge Flow Rate:

0.69 gallons per minute

Discharge Pressure:

100.0 pounds per square inch gage

Operating Speed At Rated Capacity:

11300.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.2

Discharge Connection Thread Size And Series/type Designator:

0.438-20 unf

Intake Connection Thread Size And Series/type Designator:

0.562-18 unf

Prime Mover Power Rating:

0.125 horsepower

Voltage In Volts:

208.0

Phase:

Three

Frequency In Hertz:

400.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400