## NSN 4320-00-839-1470

Hydraulic Motor - Page 1 of 2

Threaded and threaded



View Online at https://aerobasegroup.com/nsn/4320-00-839-1470

Thread Direction:
Left-hand and right-hand
Torque Load Rating:
3.6 inch-pounds
Key Length:
1.000 inches
Mounting Type:
Flange
Key Width:
0.125 inches
Mounting Hole Diameter:
0.250 inches
Mounting Hole Quantity:
4
Thread Size:
0.500-14 and 0.500-14
Shaft Diameter:
0.500 inches
Operating Speed At Rated Capacity In Rpm:
2400.0
Mounting Bolt Circle Diameter:
1.768 inches
Drive Shaft Type:
Keyed
Housing Material:
Iron, cast
Screw Thread Series Designator:
Nptf and nptf
Shaft Rotation Direction:
Clockwise and counterclockwise
Thread Location:
Internal and internal
Shaft Protrusion Length:
1.563 inches
Connection Quantity:
1 and 1
Connection Type:
Inlet and outlet
Maximum Working Pressure Rating At Specificationified Tempurature Range:
1500 at no rated temp
Connection Design:

## NSN 4320-00-839-1470

Hydraulic Motor - Page 2 of 2



Key Height:
0.125 inches
Displacement Type:
Constant
Constant Displacement Per Revolution:
0.180 cubic inches
Housing Surface Treatment:
No protective fkx
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T103-f