

View Online at <https://aerobasegroup.com/nsn/4320-00-841-4114>

Prime Mover Quantity:

1

Mounting Type:

Base

Stage Quantity:

4

Exhaust Pressure:

15.0 pounds per square inch gage

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Media For Which Designed:

Water, fresh

Power Drive Operating Pressure:

1050.0 pounds per square inch gage

Pump Quantity:

1

Maximum Discharge Flow Rate:

460.0 gallons per minute

Discharge Pressure:

1515.0 pounds per square inch gage

Total Head:

462.000 feet

Suction Lift:

55.000 feet

Operating Speed At Rated Capacity:

7600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

4

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Steam turbine

Features Provided:

Self-priming

Reference Number Differentiating Characteristics:

As differentiated by being furnished without repair parts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400