NSN 4320-00-841-9733

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-841-9733

| , , , , |
|-------------------------------------|
| Prime Mover Quantity: |
| 1 |
| Exhaust Pressure: |
| 15.0 pounds per square inch gage |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Round flange |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Round flange |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| Power Drive Operating Pressure: |
| 585.0 pounds per square inch gage |
| Pump Quantity: |
| 1 |
| Maximum Discharge Flow Rate: |
| 20.0 gallons per minute |
| Discharge Pressure: |
| 647.5 pounds per square inch gage |
| Total Head: |
| 1502.000 feet |
| Operating Speed At Rated Capacity: |
| 1150.0 revolutions per minute |
| Pumping Element Operating Position: |
| Vertical |
| Rotary Pump Design: |
| Screw |
| Prime Mover Type: |
| Steam turbine |
| Prime Mover Power Rating: |
| 17.500 horsepower |
| Specification Or Standard: |
| 3 type and m-1 class |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 4320-00-841-9733

Rotary Pump Unit - Page 2 of 2



Fiig:

A19400