

View Online at <https://aerobasegroup.com/nsn/4320-00-842-0707>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Oil

**Environmental Protection:**

Drip-proof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

380.0 gallons per minute

**Discharge Pressure:**

55.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Rotary Pump Design:**

Screw

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

39.0

**Prime Mover Power Rating:**

30.000 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

As differentiated by power unit electric motor ac, dimensionaldata 22.688 in. Lg o/a 17.500 in. Diameter o/a w/o controller

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A19400