

View Online at <https://aerobasegroup.com/nsn/4320-00-842-0707>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Oil

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

380.0 gallons per minute

Discharge Pressure:

55.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Rotary Pump Design:

Screw

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

39.0

Prime Mover Power Rating:

30.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by power unit electric motor ac, dimensionaldata 22.688 in. Lg o/a 17.500 in. Diameter o/a w/o controller

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400