NSN 4320-00-842-2627

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-842-2627

Mounting Type: Base Intake Connection Quantity: Intake Connection Type: Threaded internal Discharge Connection Quantity: Discharge Connection Type: Threaded internal Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet Operating Speed At Rated Capacity:			
Intake Connection Quantity: Intake Connection Type: Threaded internal Discharge Connection Quantity: Discharge Connection Type: Threaded internal Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Intake Connection Type: Threaded internal Discharge Connection Quantity: 1 Discharge Connection Type: Threaded internal Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Intake Connection Type: Threaded internal Discharge Connection Quantity: 1 Discharge Connection Type: Threaded internal Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Threaded internal Discharge Connection Quantity: 1 Discharge Connection Type: Threaded internal Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Discharge Connection Quantity: 1 Discharge Connection Type: Threaded internal Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Discharge Connection Type: Threaded internal Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Discharge Connection Type: Threaded internal Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Threaded internal Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Drive Connection Type: Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Rigid coupled Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Maximum Discharge Flow Rate: 1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
1.8 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
Discharge Pressure: 50.0 pounds per square inch gage Total Head: 20.000 feet			
50.0 pounds per square inch gage Total Head: 20.000 feet			
Total Head: 20.000 feet			
20.000 feet			
Operating Speed At Rated Capacity:			
1725.0 revolutions per minute			
Pumping Element Operating Position:			
Horizontal			
Pump Rotation Direction:			
Clockwise and counterclockwise			
Rotary Pump Design:			
Gear			
Operation Method:			
Powered			
Drive Shaft Type:			
Tapered			
Drive Shaft End Diameter:			
0.500 inches			
Drive Shaft Length:			
1.500 inches			
Pump Basic Material:			
Bronze			
Discharge Connection Thread Size And Series/type Designator:			
0.125-18 npt			
Intake Connection Thread Size And Series/type Designator:			

0.125-18 npt

NSN 4320-00-842-2627

Rotary Pump - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400