

View Online at <https://aerobasegroup.com/nsn/4320-00-844-8314>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Frame

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Dc

**Media For Which Designed:**

Water, salt

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

30.0 gallons per minute

**Discharge Pressure:**

135.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

350.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Rotary Pump Design:**

Vane

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

14.9

**Prime Mover Power Rating:**

5.000 horsepower

**Voltage In Volts:**

250.0

**Special Features:**

Intake and discharge flanges drilled to accommodate 1-1/2 in. Nstd flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400